

MATERIAL SAFETY DATA SHEET

GENERAL INFORMATION

PRODUCT NAME OR NU	MRFR (as it	annears on label)		CATALOG NUMBER	ı	
Noalox® Anti-Oxidar	,	All "30" Series				
MANUFACTURER'S NAM		EMERGENCY TELEPHONE NO.				
IDEAL INDUSTRIES	, INC.	(815) 895-5181				
ADDRESS (Number, Stree		e, Zip Code)		1 , ,		
Becker Place, Sycar						
	SCRIPTION, I	PROPER SHIPPING NAME, HAZARD C	LASS, HAZARD CLASS NO	., HAZARD ID NO. (49 CFR	172.101)	
None			-			
CHEMICAL DESCRIPTION			FORMULA	· · · · · · · · · · · · · · · · · · ·		
Petroleum-Based Mix	kture		Proprietary	• •		
	1	SECTION I - II	NGREDIENTS	154.4		
CAS REGISTRY NO.	%W	CHEMICA	in NTP	s a carcinogen , I ARC or OSHA (specify)		
9003-29-6	<80	Polybutene		No		
7440-66-6	20	Zinc Dust		No		
7631-86-9	<5	Silicon Dioxide		No		
		SECTION II - PI	AVSICAL DATA			
OILING POINT		SPECIFIC GRAVITY (H ₂ O=		PERCENT VOLATILE BY	VOLUME (%)	
>500°F	°C	,	1 04		` N F	
OLUBILITY IN WATER	derate	pH = 6.5 -	PERCENT SOLID BY WEIGHT (%) 100		100	
PPEARANCE AND ODOR	icelale	na-	nu	IS MATERIAL: LIQUID SOLID GEL		
	Grav	v solid paste. mild odor			AS PASTE	
		SECTION III - FIRE AND EX				
ELASH POINT 310 F		method used C.O.C	FLAMMABLE LIMITS	LEL	UEL	

Use dry chemical, carbon dioxide or foam.

Self-contained respiratory protection should be provided for fire fighters. Keep fire exposed

SPECIAL FIRE FIGHTING PROCEDURES

containers cool with water.

EXTINGUISHING MEDIA

UNUSUAL FIRE AND EXPLOSION HAZARDS Water or foam may cause a frothing reaction. (Water reacts with zinc dust). * None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R 1910.1200

SECTION IV - HEALTH HAZARD INFORMATION

			SECTION IV - HEALTH	1AZARD INFORMATION				
EFFECTS OF OVI	EREXPOSURE - Cond		o Avoid	onged contact, may cause temporary eye discomfort.				
THRESHOLD LIM								
Zinc dust or silicon dioxide as dust: 10mg/m. PRIMARY ROUTES OF ENTRY Inhalation ☐ Skin Contact ☒ Other (specify)								
	ST AID PROCEDURE	ES	Wb	a AE actividad				
SKIN CONTACT: Wash with soan and water for 15 minutes EYE CONTACT:								
INOCOTION			Flush with water	for 15 minutes				
INGESTION: Induce vomiting and consult physician or local poison control center.								
SECTION V - REACTIVITY DATA								
STABILITY	UNSTABLE		CONDITIONS TO AVOID Avoid conditions of moisture or high humidity.					
	STABLE	Χ		,				
INCOMPATIBILIT	Y (materials to avoid)		Avoid strong oxidizers,	strong acids and water				
HAZARDOUS DE	COMPOSTION PROD	UCTS:		and water.				
Excessive heat and burning may release oxides of carbon.								
HAZARDOUS POLYMERIZATION		MAY OCCUR CONDITIONS TO AVOID None						
	WILL NOT OCCU	IR)	X					
<u>I</u>			SECTION VI - SPILL AN	D LEAK PROCEDURES				
STEPS TO BE TA	KEN IF MATERIAL IS	RELE		vel or vacuum spilled material. Clean up spills immediately.				
Use absorbe	nt media.			voi oi vaodam opinioa matoriai. Cicam ap opinio immodiatory.				
WASTE DISPOSA	L METHOD	Co	omnly with Federal, state and l	ocal regulations for solid landfill.				
CERCLA (Superfu	nd) REPORTABLE QI		TY (in lbs)					
RCRA HAZARDO	US WASTE NO. (40C)	FR 261	None Re	equired				
1101011111211120	00 1111012110. (1001	201	None Re	equired				
VOLATILE ORGA	NIC COMPOUND (VC	C) (as	packaged, minus water) 120 g/l, ca	alculated				
³ Theoretical	lb/gal N/A	4		^a Analytical Ib/gal N/A				
				ROTECTION INFORMATION				
RESPIRATORY P	ROTECTION (specify							
l	OCAL EXHAUST (Sp	ecify R	ate) If TI V exceeded use Ate) Necessary above TLV	NIOSH respirator SPECIAL None				
VENTILATION MECHANICAL (General) (Specify Rate) OTHER None								
	OVES (specify type)	n closei	EYE PROTECTION (specify type)					
None normally needed -Neoprene if necessary Safety glasses or splash goggles.								
OTHER PROTEC	OTHER PROTECTIVE EQUIPMENT Eye fountain in work area is recommended.							
			SECTION VIII - SPEC	CIAL PRECAUTIONS				
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store in dry conditions at temperatures between 40 - 120 F.								
OTHER PRECAU	Store in dry conditions at temperatures between 40 - 120 F. OTHER PRECAUTIONS							
			Keep away from child	<u> </u>				
	4 4 1		SECTION IX - ADDITI					
	uct contains t I3 of EPCRA:		ollowing materials that	are subject to the reporting requirements of				
	0-66-6, Zinc D		20%					
	plicable, N.E. =	Non	e Established					
THIS MATERIAL SAFETY DATA SHEET PREPARED BY:								
	James R. MacMurdo SIGNATURE							
	•	ate Q	uality Assurance	James R. MacNeurdo				
DATE (ATE 03/10/2006							