

PVC Electrical Conduit Cement 633.txt
 MATERIAL SAFETY DATA SHEET

MSDS 0115

 Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	PVC Electrical Conduit Cement 633	HMS CODES	
		Health	3
		Flammability	3
		Reactivity	1
		PPI	B
PRODUCT CODES	55603, 55605, 55607, 55609, 55625, 55627, 55629		
CHEMICAL FAMILY	Organic		
USE	PVC Solvent Cement		
MANUFACTURER'S NAME	The RectorSeal Corporation 2601 Spenwick Drive Houston, Texas 77055 USA	EMERGENCY TELEPHONE NO.	Chemtrec 24 Hours (800) 424-9300
VALIDATION DATE	September 26, 2011	TECHNICAL SERVICE TELEPHONE NO.	(800) 231-3345
REVISION DATE	September 26, 2011		

 Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS
35	78-93-3	Methyl Ethyl Ketone	
		ACGIH TLV	200 ppm
		OSHA PEL	200 ppm
		STEL	300 ppm
20-60	109-99-9	Tetrahydrofuran	
		ACGIH TLV	50 ppm
		OSHA PEL	200 ppm
		STEL	250 ppm
20-60	108-94-1	Cyclohexanone	
		ACGIH TLV	20 ppm (skin)
		OSHA PEL	50 ppm

 Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS
 Overexposure may cause coughing, shortness of breath, dizziness, central nervous system depression, intoxication and collapse. It may cause irritation to the respiratory tract and to other mucous membranes.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS
INHALATION
 Overexposure may cause coughing, shortness of breath, dizziness, central nervous system depression, intoxication and collapse. It may cause irritation to the respiratory tract and to other mucous membranes.

EYE CONTACT
 Severely irritating. If not removed promptly, will injure eye tissue, which can result in permanent damage.

SKIN CONTACT
 Frequent or prolonged contact may irritate and cause dermatitis. Low order of toxicity.

INGESTION
 Low order of toxicity. Small amounts of the liquid aspirated into the respiratory system during ingestion, or from vomiting, may cause bronchiopneumonia or pulmonary edema.

SUMMARY OF CHRONIC HAZARDS
 Repeated or prolonged exposure may cause signs of central nervous system depression and respiratory irritation. This material has been shown to induce tumors in laboratory animals.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

 Section 4 -- FIRST AID MEASURES

If **INHALED**: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on **SKIN**: Immediately flush with large amounts of water; use soap if available. Remove contaminated clothing.

If in **EYES**: Immediately flush with large amounts of water for at least

If SWALLOWED: 15 minutes. Get prompt medical attention.
If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT 6 F (-14 C) SETA CC LEL 2% UEL 11.8%

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. If transferring this material to other containers, ground all containers to avoid static electricity buildup and discharge which may ignite flammable vapors.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues and vapors; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion-proof equipment.

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 151 F (66 C) @ 760mm Hg

SPECIFIC GRAVITY (H2O = 1): 0.96

VAPOR PRESSURE (mm Hg): 140 @ 68 F (20 C)

MELTING POINT: N/A

VAPOR DENSITY (AIR = 1): 2.5

EVAPORATION RATE (ETHYL ACETATE = 1): 6

APPEARANCE/ODOR: Clear or Gray Liquid/Pungent Odor

SOLUBILITY IN WATER: 62%

Section 10 -- STABILITY AND REACTIVITY

STABILITY: Can form potentially explosive peroxides upon long standing in air.

CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing, acidic and basic conditions.

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers, acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, HCl and fragmented hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

Section 11 -- TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS

PVC Electrical Conduit Cement 633.txt

No ingredients in this product is an IARC, NTP or OSHA Lister carcinogen. Tetrahydrofuran - The National Toxicology Program has reported that exposures of mice and rats to THF vapor levels up to 1800 ppm 6hr/day, 5 days/week for their lifetime caused an incidence of kidney tumors in male rats and liver tumors in female mice. The significance of these findings for human health are unclear at this time, and may be related to "species specific" effects. Elevated incidences of tumors in humans have not been reported for THF.

 TOXICOLOGY DATA
 Ingredient Name

 Methyl Ethyl Ketone
 Oral -Rat LD50: 2737 mg/kg
 Inhalation-Rat LC50: 23,500 mg/m3/8H
 Tetrahydrofuran
 Oral -Rat LD50: 1650 mg/kg
 Inhalation-Rat LC50: 21,000 ppm/3H
 Cyclohexanone
 Oral -Rat LD50: 1535 mg/kg
 Inhalation-Rat LC50: 8000 ppm/4H

Section 12 -- Ecological Information

 ECOLOGICAL DATA
 Ingredient Name

 Methyl Ethyl Ketone
 Food Chain Concentration Potential: None
 WATERFOWL TOXICITY: N/A
 BOD: 214%
 AQUATIC TOXICITY: 5640 mg/l/48 hr/bluegill/TLm/fresh water
 Tetrahydrofuran
 Food Chain Concentration Potential: None
 WATERFOWL TOXICITY: N/A
 BOD: N/A
 AQUATIC TOXICITY: N/A
 Cyclohexanone
 Food Chain Concentration Potential: None
 WATERFOWL TOXICITY: N/A
 BOD: N/A
 AQUATIC TOXICITY: N/A

Section 13 -- DISPOSAL CONSIDERATIONS

 Waste Classification: RCRA classified hazardous waste. Dispose of absorbed materials and liquid waste in approved, controlled incineration facility in accordance with all local, state and federal regulations.
 Disposal Method: Incineration

Section 14 -- TRANSPORTATION INFORMATION

 DOT: Adhesives, Class 3, UN 1133, PG II, ERG#127.
 Quarts and less: Consumer Commodity, ORM-D
 OCEAN (IMDG): Adhesives, Class 3, UN 1133, PG II, IMDG#3174, EMS#3-05, MFAG#330
 Quarts and less: Adhesives, Class 3, UN 1133, PG II, Limited Quantities or Ltd Qty
 AIR (IATA): Adhesives, Class 3, UN 1133, PG II, ERG#127
 WHMIS (CANADA): Class B-2

Section 15 -- REGULATORY INFORMATION

 REGULATORY DATA
 Ingredient Name

 Methyl Ethyl Ketone
 SARA 313 Yes
 TSCA Inventory Yes
 CERCLA RQ 5,000 lb.
 RCRA Code U159
 Tetrahydrofuran
 SARA 313 No
 TSCA Inventory Yes
 CERCLA RQ 1,000 lb.
 RCRA Code U213
 Cyclohexanone
 SARA 313 No
 TSCA Inventory Yes

PVC Electrical Conduit Cement 633.txt
5,000 lb.
U057
CERCLA RQ
RCRA Code

=====
Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001